

Fujitsu recommends Windows® 7.

# Data Sheet

## Fujitsu ESPRIMO C700 Desktop PC

The Ultra Small Professional PC

The Fujitsu ESPRIMO C700 has an ultra-small form factor with a volume of less than 8-liters, making it ideal for your space-constrained office. A 92%-efficient power supply and Intel® Advanced Manageability will lower your energy and administrative costs. A professional Intel® core™ processor ensures great performance. Plus, EraseDisk ensures secure system retirement.



### Compact design

Top quality PC for office environments with little space; can be positioned both horizontally and vertically

- Ultra small form factor PC with only 7.4 liters volume, integrated, highly efficient power supply, legacy interfaces and powered serial ports

### Highest energy efficiency coupled with intelligent performance

Low power consumption combined with top performance

- 2nd generation Intel® Core™ processors with Turbo Boost 2.0 and Hyper-Threading technology, energy efficient power supply up to 90% and ENERGY STAR® certification

### Compact but expandable

Smallest Fujitsu ESPRIMO PC system with discrete graphics card supporting multi-monitoring

- Up to a 500 GB disk and PCIe x16 slot



### Family concept

Reduced test and evaluation costs for the existing PC infrastructure

- Uniform technology platform and bit image for the Fujitsu 700 series



# Components

<b>Processor</b>	Intel® Core™ i7-2600 processor (4 Cores / 8 Threads, 3.40 GHz, 8 MB, Intel® HD Graphics 2000) Intel® Core™ i5-2500 processor (4 Cores / 4 Threads, 3.30 GHz, 6 MB, Intel® HD Graphics 2000) Intel® Core™ i5-2400 processor (4 Cores / 4 Threads, 3.10 GHz, 6 MB, Intel® HD Graphics 2000) Intel® Core™ i3-2120 processor (2 Cores / 4 Threads, 3.30 GHz, 3 MB, Intel® HD Graphics 2000) Intel® Core™ i3-2100 processor (2 Cores / 4 Threads, 3.10 GHz, 3 MB, Intel® HD Graphics 2000) Intel® Pentium® processor G850 (2 Cores / 2 Threads, 2.90 GHz, 3 MB, Intel® HD Graphics) Intel® Pentium® processor G840 (2 Cores / 2 Threads, 2.80 GHz, 3 MB, Intel® HD Graphics) Intel® Pentium® processor G620 (2 Cores / 2 Threads, 2.60 GHz, 3 MB, Intel® HD Graphics) Intel® Celeron® processor G530 (2 Cores / 2 Threads, 2.40 GHz, 2 MB, Intel® HD Graphics)
<b>Operating systems</b>	
<b>Operating system</b>	Genuine Windows® 7 Home Basic (EM) 32-bit Genuine Windows® 7 Home Premium 64-bit Genuine Windows® 7 Professional 32-bit Genuine Windows® 7 Professional 64-bit
<b>Operating system compatible</b>	openSUSE Linux Genuine Windows Vista® Genuine Windows® XP
<b>Operating system notes</b>	Limited Windows® XP support. Microsoft discontinued Windows® XP certification on system level, basic drivers via <a href="http://support.ts.fujitsu.com">http://support.ts.fujitsu.com</a>
<b>Memory modules</b>	2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1333 MHz, PC3-10600, DIMM 4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1333 MHz, PC3-10600, DIMM
<b>Hard disk drives (internal)</b>	SSD SATA, 128 GB, 2.5-inch mSATA, 16 GB, Flash drive mSATA, 8 GB, Flash drive mSATA, 4 GB, Flash drive mSATA, 2 GB, Flash drive HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch HDD SATA III, 7200 rpm, 500 GB, 3.5-inch, business critical HDD SATA III, 7200 rpm, 500 GB, 3.5-inch HDD SATA III, 7200 rpm, 320 GB, 3.5-inch HDD SATA II, 7200 rpm, 160 GB, 2.5-inch HDD SATA, 320 GB, 2.5-inch
<b>Hard disk notes</b>	Up to 18 GB of HDD space is reserved for system recovery
<b>Graphics add on cards (optional)</b>	NVIDIA® Quadro® NVS 300 LP, 512 MB NVIDIA® GeForce® 405 display port low profile, 512 MB LFH59/ 2x DVI-I adapter cable LFH59/ 2x DP adapter cable DP to DVI-D (single link) Adapter Cable
<b>Drives (optional)</b>	DVD Super Multi DVD Super Multi Slot-in slim

**Interface add on cards/components  
(optional)**

WLAN III, 802.11g/Draft-n (Windows only)  
 USB 3.0 PCIe x1  
 Parallel Interface  
 Gigabit Ethernet PCIe x1, DS  
 eSATA Interface  
 Dual serial card PCIe x1, powered  
 Dual serial card PCIe x1

**Base unit** ESPRIMO C700

**Mainboard**

**Mainboard type** D3064  
**Formfactor** proprietary  
**Chipset** Intel® Q65  
**Processor socket** LGA 1155  
**Processor quantity maximum** 1  
**Memory slots** 4 DIMM (DDR3)  
**Supported capacity RAM (max.)** 32 GB  
**Memory frequency** 1333 MHz  
**Memory notes** Dual channel support.  
 For dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules).  
 > 16 GB support with future memory modules

**LAN** 10/100/1000 MBit/s Intel® 82579 V

**BIOS version** AMI Aptio 4.6

**BIOS features** BIOS Flash EPROM update by software  
 Recovery BIOS  
 Unified Extensible Firmware Interface (UEFI)

**Audio codec** Conexant CX20642

**Audio features** Internal speaker supports audio playback, High Definition audio

**I/O controller on board**

**Serial ATA total** 3  
**Controller functions** Serial ATA II (3 Gbit)  
 Serial ATA III (6 Gbit)  
 NCQ  
 AHCI

**Interfaces**

**Audio: line-in** 1  
**Audio: line-out** 1  
**Front audio: microphone** 1  
**Front audio: headphone** 1  
**USB 2.0 total** 12  
**USB 3.0 total** optional  
**USB front** 4  
**USB rear** 6  
**USB internal** 2  
**VGA** 1 (via DVI to VGA adapter, part of shipment)  
**DisplayPort** 1  
**DVI** 1 (DVI-I)  
**Serial (RS-232)** 2 (powered, 9pin, 16 byte FIFO, 16550 compatible)  
**Mouse / Keyboard (PS/2)** 2  
**Ethernet (RJ-45)** 1  
**Parallel** 1 (optional) (25pin with EPP and ECP)

**Interfaces**

eSATA	1 (optional)
Interface Module notes	Anytime USB charge functionality

**Input device / components**

Input devices (optional)	Optical USB tilt wheel mouse Optical USB/PS2 tilt wheel mouse KBPC PX ECO
--------------------------	---

**Drive bays**

Drive bays total	2
3.5-inch internal bays	1
5.25-inch external bays	1
Drive bay notes	slim optical disc drive

**Slots**

PCI-Express 2.0 x16	1 x (220 mm) Low profile
---------------------	--------------------------

**Graphics on board**

Graphics brand name	Intel® HD Graphics or HD Graphics 2000 (depending on CPU)
Shared video memory	up to 1759 MB
TFT resolution (VGA)	1024 x 768 pixel 1280 x 1024 pixel 1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1600 x 1200 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel
TFT resolution (DVI)	1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel
TFT resolution (DisplayPort)	1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel 2560 x 1440 pixel 2560 x 1600 pixel
Graphics features	Dual display support DirectX 10.1 HDCP support OpenGL® 2.1 For multi monitoring mode, graphics card and integrated graphics run in parallel (Microsoft® Windows 7® only)
Graphics notes	Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz

**Electrical values**

Power efficiency note	power supply efficiency (at 230V; 20% / 50% / 100% load) : 87% / 90% / 87%
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Operating voltage range	90 V - 264 V
Operating line frequency range	47 Hz - 63 Hz

**Electrical values**

Max. output of single power supply	225 W
Power factor correction/active power	active
Monitor outlet	No

**Power consumption**

Power consumption note	See white paper Energy Consumption
------------------------	------------------------------------

**Heat dissipation**

Heat dissipation notes	See white paper Energy Consumption
------------------------	------------------------------------

**Noise for standard configuration (HDD, ODD)**

Noise emission	According to ISO9296
Related Processors for noise	Core i3-2100 ; Core i5-2400
Noise Operation mode 1: ODD load (Blue angel requirement)	4.6 B / 32 dB(A) ; 4.8 B / 32 dB(A)
Noise Operation mode 2: HDD load (Blue angel requirement)	3.6 B / 22 dB(A) ; 3.6 B / 22 dB(A)
Noise Operation mode 3: CPU 90% load (Blue angel requirement)	3.6 B / 22 dB(A) ; 3.9 B / 25 dB(A)
Noise Operation mode 4: High load	3.7 B / 22 dB(A) ; 4.0 B / 25 dB(A)
Noise Operation mode 5: Office applications 2.0	3.6 B / 22 dB(A) ; 3.7 B / 22 dB(A)
Idle mode (Blue Angel requirement)	3.6 B / 22 dB(A)
Noise notes / description	A weighted sound power level L <sub>wad</sub> (in B) / workplace related A-weighted sound pressure level L <sub>pAm</sub> (in dB(A)), Bystander position

**Dimensions / Weight / Environmental**

Dimensions (W x D x H)	265 x 315 x 88 mm
Operating position	Vertical / horizontal (no feet needed)
Weight	approx. 9 kg
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	10 - 35°C

**Compliance**

Product	ESPRIMO C700
Model	USD
Germany	TÜV GS
Europe	CE Nordic Swan
USA/Canada	FCC Class B CSA
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® EPEAT® Gold (dedicated regions)
Compliance link	<a href="https://sp.ts.fujitsu.com/sites/certificates/">https://sp.ts.fujitsu.com/sites/certificates/</a>

**Additional Software**

Additional software (preinstalled)	Nero Essentials S (burning software) Fujitsu Recovery (Hard Disk Based Recovery) Norton Internet Security (incl. Firewall) 60 days version Microsoft® Office Starter: reduced-functionality Word and Excel® only, with advertising. No PowerPoint® or Outlook®. Buy Office 2010 to use the full-featured software.
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) Nero 9 Essentials XL

**Miscellaneous**

Keyboard on (Special Fujitsu keyboard required)  
Thermal management  
Extended lifetime

**Compatibility (references)**

DMI 2.0  
PC 2001  
WMI 1.5  
USB 2.0  
SMBIOS

**Manageability****Manageability technology**

DeskUpdate Driver management  
PXE 2.1 Boot code  
Wake up from S5 (off mode)  
Intrusion switch (optional)  
Intel® Standard Manageability

**Manageability software**

DeskView 10.x client management including:

**DeskView components**

On/Offline remote client management  
Detailed system inventory management and reports  
BIOS Management  
Remote power management  
System notifications  
Security Remote Control  
DeskView Helpdesk Integration  
WoL (Wake on LAN)

**Manageability link**

<http://ts.fujitsu.com/manageability>  
<http://www.altiris.com/fujitsu>

**Security****System protection**

Kensington Lock support  
Eye for padlock  
Optional: Integrated cabinet lock

**Audit proof protection**

EraseDisk (optional)  
Boot sector virus protection  
Write protect option for the Flash EPROM  
Embedded security (TPM 1.2)  
Control of all USB interfaces  
External USB ports can be disabled separately  
Control of external interfaces

**Access protection**

User and supervisor BIOS password  
Hard disk password  
Optional: Access protection via external SmartCard reader  
Optional: Access protection via internal SmartCard reader

**Serviceability**

EasyFix  
EasyChange for HDD

**Packaging information****Packaging dimension**

467x265x540 mm

**Max. quantity / pallet**

28

**Material - Weight (g) Carton**

940 g

**Material - Weight (g) EPS / PS**

190 g

**Material - Weight (g) PE**

appr. 60 g

**Packaging notes**

printed user documentation is bleached in chlorine free process

**Warranty****Standard Warranty**

1 year

---

**Warranty**

**Service level** Bring-In / On-Site Service (depending on country)

**Maintenance and Support Services - the perfect extension**

**Recommended Service** 5x9, Response Time: Next Business Day

**Spare Parts availability** 5 years

**Service Weblink** <http://ts.fujitsu.com/Supportservice>

## More information

### Fujitsu platform solutions

In addition to Fujitsu ESPRIMO C700, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

#### Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

#### Computing Products

[www.fujitsu.com/global/services/computing/](http://www.fujitsu.com/global/services/computing/)

#### Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

### More information

Learn more about Fujitsu ESPRIMO C700, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.  
<http://ts.fujitsu.com/ESPRIMO>

### Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at <http://www.fujitsu.com/global/about/environment/>



### Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see [http://ts.fujitsu.com/terms\\_of\\_use.html](http://ts.fujitsu.com/terms_of_use.html)  
Copyright © Fujitsu Technology Solutions

### Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

#### Contact

FUJITSU Technology Solutions  
Website: <http://ts.fujitsu.com>  
2011-12-20 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see [http://ts.fujitsu.com/terms\\_of\\_use.html](http://ts.fujitsu.com/terms_of_use.html)  
Copyright © Fujitsu Technology Solutions